



ESP SAFETY INC

Technology of the Future
Protection for Today

ESP Safety has designed its ITES-Dual Test Lamp to help with the functional testing of our IPES Flame Detectors without removing them from the application.

The ITES-Dual Test Lamp generates directed modulated radiation with the sufficient intensity to signal a flame or fire response on our IPES Flame Detectors. A flame or fire response is indicated by a continuous LED on our IPES Flame Detectors.

We guarantee the trouble-free operation of the ITES-Dual Test Lamp for the first year. Each ITES-Dual Test Lamp is supplied pre-assembled and includes batteries, an emission source for checking other types of power sources, and an Operating Manual.

Features

- 1 Year warranty
- Easy to use
- Lightweight
- Portable
- Explosion proof mark 2ExeibIIBT4 X



**ITES-Dual
TEST LAMP**

Specifications

Batteries	Three "D" Cell Alkaline or equivalent
Weight	2.20 lbs (1.0 kg with batteries)
Operating Distance	9.84 ft (3m)
Operating Time	One hour of constant use
Operating Temperature Range	-40°F to +140°F (-40°C to +60°C)
Storage Temperature Range	-40°F to +140°F (-40°C to +60°C)
Certifications	2ExeibIIBT4 X

Ordering Information

Product #	Description:
120-0007	For all IPES Detectors (UV, IR/UV, IR3)



80024-001
R03

CONTACT
www.espsafetyinc.com
info@espsafetyinc.com

CALIFORNIA
555 N. First Street | San Jose, CA 95112
Ph: +1-408-886-9746 | Fx: +1-408-886-9757

TEXAS
4001 W. Sam Houston Parkway N. Ste #150 | Houston, TX 77043
Ph: +1-713-999-1050 | Fx: +1-713-999-1060