



**ESP SAFETY INC**

Technology of the Future  
Protection for Today

ESP Safety's Vector model field control unit performs as an integrated control terminal and display for ESP Safety's gas detector product line. The Vector can operate as a stand-alone display for a variety of our gas detectors which can be remotely located up to 500 feet away. A sensor head can also be attached directly to the display housing to produce a unified detector/display unit.

### Key Features

- Vivid 2.7" (diagonal) 128x64 pixel resolution, OLED screen simultaneously display a wide range of data including gas concentrations, alarm levels, faults and operational modes
- Analog 4-20 current loop with HART, Digital RS- 485 Modbus RTU, and 4 relays are standard data communication channels of the Vector
- Non-intrusive, onsite detector calibration via HART Field Communicator or Magnetic Wand
- Operating Temp Range of -58°F to +167°F (-50°C to +75°C)
- Configurable to control & monitor up to two detectors
- SIL-2 certification by independent 3rd party agency NRTL
- 316 Stainless Steel construction, Explosion-Proof Housing, Class1, Division 1



SIL 2Rated



# VECTOR GAS DETECTOR

### Applications

- Offshore platforms
- Shipping tankers, freighters, and other vessels
- LNG/LPG processing & storage facilities
- Oil & gas refineries
- Petrochemical plants
- Gas & electric utilities

### Features and benefits

- Tri-color status LED indicates operational mode, fault, and gas presence.
- 4 indicators: 3 warning & alarm level LEDs, and 1 calibration LED
- 128 x 64 pixel OLED display providing continuous graphical indication of trending data for Peak Reading and Time-Weighted Average (TWA) of gas concentration
- Remote sensor option allows the user to either connect the Vector up to 500 feet away or install the unit at the site of the potential hazard
- Robust construction and heated optics withstand harsh environments
- Plug-in, pre-calibrated (field replaceable) gas sensors
- Enhanced temperature range
- 5 year warranty

#### CONTACT

www.espsafetyinc.com  
info@espsafetyinc.com

#### CALIFORNIA

555 N. First Street | San Jose, CA 95112  
Ph: +1-408-886-9746 | Fx: +1-408-668-0848

#### TEXAS

4001 W. Sam Houston Parkway N. Ste #150 | Houston, TX 77043  
Ph: +1-713-999-1050 | Fx: +1-713-999-1060

**Electrical Characteristics**

- Voltage** +24VDC Nominal (+18 to 32 VDC)
- Power** 4.3 W standby, <5.3 W during alarm  
12.0W with heater on (temp≤30°F)
- Outputs** 1) Analog signal: 2x+4-20mA  
2) Digital RS-485, Modbus RTU  
3) HART communication port  
4) Three User Programmed Alarm Relays,  
One Fault Relay

**Technical Specifications**

- Humidity** 0 to100% relative humidity, noncondensing
- Operating Temperature** -58°F to +167°F (-50°C to +75°C)
- Storage temperature** -76°F to +185°F (-60°C to +85°C)
- Ingress Protection** IP 66
- SIL Rating** SIL 2

**Mechanical Characteristics**

- Material** Aluminum and 316L Stainless Steel
- Conduit Connection** 2 Conduit Entries 3/4"NPT
- Dimensions** 10.7"x 5.9"x 4.8" \*\*(Vector + PGU)
- Weight** 14 lbs (6.4 kg)
- Housing Warranty** 5 years

**Certifications**

**FM APPROVED**  
 Class I, Division 1  
 Groups B, C & D T4Ta=-58°F to +167°F (-50°C to +75°C) IP66

**Ex**  
 Exd IIC T4  
 -58°F to +167°F (-50°C to +75°C) IP66

**IEC IECEx**  
 Ex d IIC T4  
 -58°F to +167°F (-50°C to +75°C) IP66

**SP**  
 Class I, Division 1 Groups B, C & D T4Ta=-58°F to +167°F (-50°C to +75°C) IP66

**SIL2 Rated**

Sensor's Type	Gas	Gas Formula	Detected Component Measuring Range	Accuracy	Response Time	
Plug-in universal gas sensors optic infrared PGU-IR	Methane	CH4	(0-100) % LEL	± 2% full scale	T20<5seconds T90<25seconds	
	Propane	C3H8				
	Ethylene	C2H8				
	Hexane	C6H14				
	Butane	C4H10				
	Isobutane	I-C4P10				
	Ethanol	C2H5OH				
	Cyclopentane	C5H10				
	Propylene	C3H6				
	Methanol	CH3OH				
	Gasoline Vapor	*				
	Diesel Vapor	*				
JP4 Vapor	*					
Plug-in universal gas sensors photoionized PGU-P	Carbon Dioxide	CO2	(0-2) % vol. (0-5) % vol. (0-3000) ppm	± 2% full scale	T50 <3seconds T90 <5seconds	
	Isobutylene	C4H8	(0-20) ppm (0-200) ppm (0-2000) ppm	± 2% full scale	T20<5seconds T90<25seconds	
	Benzene	C6H6	(0-100) ppm (0-1000) ppm (0-10000) ppm	± 2% full scale	T50<9seconds T90<25seconds	
	Ethylene	C2H4	(0-20) ppm (0-2000) ppm	± 2% full scale	T50<9seconds T90<25seconds	
Plug-in universal gas sensors electrochemical PGU-E	Methyl mercaptan	CH3SH	(0-100) ppm Other ranges per request	± 2% full scale	T90 <25 seconds	
	All gases with ionization potential <10.6 eV					
	Hydrogen Sulfide (MOS)	H2S	(0-100) ppm	± 2% full scale	T90 <20 seconds	
	Oxygen	O2	(0-30) % vol.	± 2% full scale	T90 <11 seconds	
	Carbon monoxide	CO	(0-100) ppm (0-500) ppm (0-1000) ppm	± 2% full scale	T20<10seconds T90<25seconds	
	Hydrogen sulfide	H2S	(0-50) ppm	± 2% full scale	T20 <6 seconds T50 <10 seconds T90 <15 seconds	
	Hydrogen sulfide	H2S	(0-100) ppm	± 2% full scale	T50 <3 seconds T90 <7 seconds	
	Nitrogen dioxide	NO2	(0-20) ppm	± 2% full scale	T50<12seconds T90<25seconds	
	Sulfur dioxide	SO2	(0-20) ppm (0-100) ppm	± 2% full scale	T50<12seconds T90<25seconds	
	Ammonia	NH3	(0-100) ppm	± 2% full scale	T90 <60 seconds	
	Chlorine	Cl2	(0-20) ppm	± 2% full scale	T90 <25 seconds	
	Hydrogen chloride	HCl	(0-30) ppm	± 2% full scale	T50<30seconds T90<90seconds	
	Hydrogen fluoride	HF	(0-10) ppm	± 2% full scale	T50<30seconds T90<90seconds	
Formaldehyde	CH2O	(0-10) ppm	± 2% full scale	T50 <20 seconds		
Methanol	CH3OH	(0-100) ppm	± 2% full scale	T90 <90 seconds		
Plug-in gas universal gas sensors Catalytic PGU-C	Hydrogen	H2	(0-4)%vol. (100%LEL) (0-100) ppm (0-1)%	± 2% full scale	T50 <5 seconds T90 <8 seconds	

